


# HGUIDE n500 INERTIAL NAVIGATOR



*Proven – Dependable – Accurate*

The HGuide n500 is the world's first Navigation Grade BYOG (Bring Your Own GNSS) all-attitude navigator to support continuous position and attitude navigation, even required even during regular prolonged GNSS outages.

The HGuide n500 is built on Honeywell's leading-edge HG4930 IMU plus the widely accredited Honeywell HGuide Sensor Fusion (HGSF) software.

Honeywell's integration expertise blends the data from the IMU and data from a customer-supplied GNSS receiver to provide accurate, robust navigation service with all the functionalities that you need in an ultra-low SWaP form factor.

The HGuide n500 output data includes timestamped position, velocity, angular rate, linear acceleration, roll, pitch, and heading information.

In dual-antenna mode, the n500 supports GNSS-based heading measurements and initialization.

## KEY HONEYWELL ADVANTAGES

- Honeywell proven navigation algorithms for Air, Land, and Sea
- World-class inertial sensor development, calibration, and compensation
- Proven reliability, dependability, and ruggedness. MTBF=80,000rs
- Highest-performing Inertial/Navigator of its size, weight, and price
- Compatible with multiple GNSS receivers, including HGuide g080 from Honeywell
- Multiple communication ports
- Accurate attitude performance that provides better quality navigation trajectories
- The HGuide n500 inertial navigation system is not ITAR controlled. Its Export Control Classification Number (ECCN) is 7A994 and is generally available free of an export license

## HGUIDE n500 TYPICAL KEY CHARACTERISTICS

Compatible Receivers	Honeywell HGuide g080 u-Blox F9 Series	Novatel OEM7 Septentrio AsteRx Series
Shock/Vibration	40 G for 11 msec (MIL-STD-810G) / Random 7.7 g's RMS, 20-2000 Hz	
Supply Voltage/Power	+5 VDC +/- 5%, 3 Watts typical	
Weight/Size	140 grams, 65 x 51 x 35.5 mm	
Temperature	-40° C to +85° C	
Communication Ports	3 x 5V CMOS (UART)	
Discrete Signals	System & GPS Time Marks, User Event In (2), 1 PPS Event In Marker, Supports Lidar	

## HGUIDE n500 NAVIGATION PERFORMANCE <sup>1,2</sup>

POSITION		VELOCITY		HEADING	PITCH/ROLL
Horizontal (m, 1σ)	Vertical (m, 1σ)	Horizontal (m, 1σ)	Vertical (m, 1σ)	(°, 1σ)	(°, 1σ)
< 0.01 RTK < 0.4 SBAS	0.025 RTK 0.40 SBAS	< 0.015	< 0.01	.03	< 0.015

<sup>1</sup> In dual antenna mode with 2m baseline; longer baselines improve performance

<sup>2</sup> Position and Heading performance may be dependant on GNSS receiver selected and environmental

## HGUIDE n500 RTK DUAL ANTENNA PERFORMANCE – GNSS OUTAGES BY DURATION <sup>3,4,5,6,7,8</sup>

RMS Error	3 Seconds	10 Seconds	30 Seconds	60 Seconds
Horizontal (m)	0.08	0.10	1.0	3.5
Vertical (m)	0.05	0.10	0.30	0.70
Heading (°)	0.01	0.03	0.04	0.05
Horizontal Velocity (m/s)	0.02	0.04	0.06	0.45
Vertical Velocity (m/s)	<0.01	0.01	0.02	0.03

<sup>3</sup> Unit accepts DMI aiding via an HGNSI message

<sup>4</sup> HGUIDE MOTION DETECT and LAND VEHICLE CONSTRAINTS improve Land Vehicle performance during GNSS outages even without an Odometer (DMI)

<sup>5</sup> Typical Horizontal RMS Error of ~0.25% of distance traveled with Land Vehicle Constraints and Zero Velocity Detect enabled, but no DMI input

<sup>6</sup> Statistics are calculated by taking the RMS of the maximum error over multiple complete GNSS outages in a Land Vehicle application

<sup>7</sup> GNSS Receiver used was in RTK GNSS mode before and after outages

<sup>8</sup> SBAS error growth will be similar, but absolute accuracy will be reduced

## GNSS OUTAGES BY DISTANCE PER AIDING SOURCE <sup>9</sup>

DMI	Horizontal RMS Error	<0.05% of distance traveled
DVL	Horizontal RMS Error	<0.2% of distance traveled

<sup>9</sup> Details of qualification tests and sensors used available on request

## ONBOARD IMU SPECIFICATION

Spec	Gyro	Accel
Range	+/- 400 °/s	+/- 20g
Bias	7 °/hr 1σ	1700 μg 1σ
Bias Stability	0.25 °/hr 1σ	25 μg 1σ
Random Walk	0.04 °/√hr	0.045 m/s/√hr

## ACCESSORIES AVAILABLE

- HGuide n500 IO Interface Card
- GNSS antennas and cables with Survey and UAV grade options
- HGuide Data Reader, SDK and ROS Drivers to support easy integration



### For More Information

HGuide.com

HGuide.sales@honeywell.com

### Honeywell Aerospace

1944 E Sky Harbor Circle

Phoenix, AZ 85034

aerospace.honeywell.com



4/22

© 2022 Honeywell International Inc.

THE  
FUTURE  
IS  
WHAT  
WE  
MAKE IT

**Honeywell**