HGUIDE 1400 INERTIAL MEASUREMENT UNIT

Inertial Innovation Inside

KEY HONEYWELL ADVANTAGES

- Sub 1° Gyro performance tactical grade IMU in an extremely small package
- World-class inertial measurement unit development, full temperature range calibration and compensation from the world's premier high grade IMU manufacturer
- Units feature a range of configurable options for output data rates, baud rates and filtering formats
- Provides Roll and Pitch information in addition to standard Inertial Sensor data
- Proven reliability, dependability and ruggedness, through unit life

HGUIDE 1400 IMU KEY CHARACTERISTICS					
Size/Volume	28mm x 25mm x 13mm / <8cu cm				
Weight	9 grams				
Power Consumption	<0.5 Watts				
Operating Temperature Range	-40°C to 85°C				
Data Rate	Up to 600Hz Inertial Data, 1800Hz Control Data Default 100Hz Roll and Pitch Output				
Gyro Operating Range	+/- 490 deg/s in all axes				
Accelerometer Operating Range	16g in all axes				
Supply Voltages	+4.5 to +15 VDC				
Bandwidth	200 Hz at -3dB (Output Frequency dependant)				
Vibration	Random : 20-2000Hz MIL-STD-810G 2.2 grams				
Shock	40g, 11ms per MIL-STD-810G				
Communication Protocols	RS-422 differential and 3.3V TTL UART				
Asynchronous Baud Rate	921.6 Kbs default				
Discrete Signals	Data ready output				

HGUIDE 1400 IMU PERFORMANCE – ROOM TEMPERATURE								
Gyro Bias (°/hr 10)	Gyro Bias In-run (°/hr 1σ)	ARW (°/√h r)	Accel Bias (mg 1 _o)	AccelBias In-run Stability (mg 10)	VRW (m/s/√hr)	Pitch/Roll (°)		
50	0.75	0.075	2.0	0.01	0.012	Static = 0.1 Dynamic = 0.2		

The HGuide i400 is an advanced microelectromechanical system (MEMS) based inertial measurement unit (IMU) engineered to fulfill the demands of applications requiring exceptional performance within a compact, lightweight, and rugged form factor. Equipped with industry-standard communication interfaces and boasting a wide-input voltage range, the HGuide i400 seamlessly integrates into diverse architectures. Its remarkably small size, low weight, and low power consumption make the HGuide i400 suitable for a wide range of applications from 3D Mapping to Autonomy to AUVs.

The IMU incorporates MEMS gyroscopes and accelerometers while utilizing a mechanical design to help mitigate unwanted inputs commonly encountered in real-world scenarios. Proprietary design elements enable the HGuide i400's ruggedness, meeting the requirements of even the most exactingusers.

The HGuide i400 outputs Honeywell proprietary binary data (HGNSI) per other Honeywell HGuide IMUs.

Honeywell support also includes access to ROS drivers, SDK and HGuide Data Reader.

Manufactured and dispatched from a Honeywell facility, the HGuide i400 is generally accessible without export controls.

For more information

HGuide.com or email us at: HGuide.sales@honeywell.com

Honeywell Aerospace

2600 Ridgeway Parkway Minneapolis, MN55413 aerospace.honeywell.com Honeywell