Honeywell











Sky Connect[™] Tracking System

Manage your fleet with a complete Iridium[®] satellite tracking and communications solution

A complete system that helps you manage your fleet.

The single best way to maximize safety and efficiency for demanding missions is with a complete system that helps you actively manage your fleet.

Sky Connect[™] Tracking System is the industry's only complete tracking and communications solution with features and benefits you won't find anywhere else.



Text and Talk

Designed for crews with a busy workload, the Sky Connect system easily accommodates any operational scenario with its talk and text capabilities.

Sky Connect text messaging provides the easiest and quickest way for pilots and dispatchers to communicate simple messages to one another.

The prestored messages with data fields and full telephone keypad make text messaging with the MMU-II[™] an excellent way to communicate up-to-date, accurate information.

Messages sent to the aircraft by the dispatcher are displayed immediately and all messages received during the flight can be recalled.

When equipped with the MMU-II, the Sky Connect system can also include a voice telephone.

The system provides a headset-level interface tied into the aircraft audio panel and supports over 500 prestored phone numbers with names for easy use.

Total Situational Awareness

Sky Connect Tracking System enables any equipped aircraft in the world to be tracked in real time via the Iridium satellite network.

The lightweight transceiver LRU sends encrypted GPS-based position reports at automated intervals to authorized control centers using secure data protocols.

The Sky Connect Map web-based software displays the aircraft location, GPS flight plan, crew status and weather overlays on topographical maps for full situational awareness.

Text messages from the aircraft are displayed on the mapping screen so dispatchers can stay organized and fleets can be managed effectively.

For integrated operations, Sky Connect offers a versatile architecture of interfaces and inputs that work with any aircraft situational display software.

System Functionality

In addition to the basic Iridium® functions (voice/ tracking/messaging), Tracker III incorporates the following capabilities:

- Shared antenna signaling for GPS and Iridium
- Integrated dual ARINC429 interfaces
- Web browserbased installation configuration
- POTS and 4-wire audio versions
- Over-the-air configuration
- Internal recording of high-res path data for post-flight review
- Transmission of high-res position data (TrueMiles[™])
- Ability to send last position/power-down report after power loss (LPV PowerBank)
- Operation in extreme environments down to -55°C

Key Features

- Tracking worldwide near real-time tracking of aircraft status, 3D location, flight route, ETA
- Text worldwide two-way text messaging
- Voice worldwide always-available voice telephone service
- Dual Voice two separate voice telephone channels one for the flight crew, one for the cabin
- Dual Mode simultaneous tracking and voice services, with uninterrupted continual provision of both services

Next-generation mission management.

Sky Connect Tracker III, the heart of the aircraft operator's mission management system, is the newest member of the Sky Connect Tracker family. This feature-rich, next-generation successor boasts exciting new capabilities and a built-in path for future upgrades.

Easily installed on any aircraft platform, Tracker III is ideal for current Sky Connect Tracker customers, those using other systems, or anyone seeking a superior mission management system. Tracker III is the new technology core of the proven and trusted Sky Connect family, ensuring excellence in reliability, service and support.

Small and Powerful

Compact systems have always been a key benefit of Sky Connect Tracker products. New technology has made it possible to increase the Tracker III's communications capabilities while also integrating the previously separate ARINC 429 converter unit. In fact, the new line replaceable unit (LRU) will fit existing installation trays, simplifying upgrades to the Tracker III for existing Sky Connect customers.

The Tracker III is an enhancement of its robust predecessor, providing significantly more capability within virtually the same form factor:

- Simultaneous tracking and voice capabilities allow vital tracking and urgent text messages to occur even during lengthy voice calls.
- A new capability called Last Position Vector (LPV) PowerBank enables the helicopter to send final position reports after the pilot powers down the aircraft or if any incident interrupts aircraft power.
- Installation is quick and easy with little disruption to operations. The new LRU fits the existing tray and wiring with minimal or no changes.
- A new OLED multipurpose display replaces LED status lights and enables simplified installation, configuration, status monitoring and troubleshooting.
- Provides FDM compliance for FAA rule 135.607 for HEMS operators.

The Tracker III also incorporates a Flight Data Monitoring function. It provides a means of collecting data from on-board systems through various interfaces to record and communicate aircraft performance and potential maintenance needs. User-configurable alerts can be generated based on threshold exceedance. Alert messages are communicated to the ground operations center using the Iridium satellite network.

Key Features

- Can be configured to capture parameters such as including: air speed, attitude, fuel flow, torque, temperature, oil pressure
- Ability to capture an additional 70 recorded parameters
- Easily downloaded data provides for quick analysis and maintenance decision making
- Reliable, globally-available Iridium satellite mission management system
- Concurrent talk, text and tracking in a single dual channel box
- Real time, secure, position reporting and event alerting for true fleet situational awareness



Sky Connect Tracker III can be integrated with Onboard Health and Usage Monitoring System (HUMS)

Key Features

- Reliable, globally-available Iridium satellite mission management system
- Concurrent Talk, text or tracking in a single box
- Encrypted GPS position reports for fleet tracking
- HUMS and vibration analysis enables maintenance based on condition
- Provides real time vibration exceedance alerts to ground crews
- Post flight web service support for flight data monitoring, fleet health trending and diagnostics

Benefits

- Optimize your mission Real time messaging, integrated flight planning, routing efficiency
- Prepare for repairs before you land Reduced downtime and faster return to service
- Single billing for all services simplifies support
- Increased safety proactive identification of faults or failures to prevent accidents
- Reduce maintenance cost via HUMS fewer spares and test flights, faster diagnosis



| SKY CONNECT TRACKER SYSTEM | | |
|-------------------------------------|------------------------------------------------------------------|--|
| MMU-II™ | | |
| Display: | Dimmable 2-line, 32-character alphanumeric | |
| Keypad: | Backlit elastomeric keys | |
| Controller: | Push/turn multifunction mode controller | |
| Memory: | High capacity directory with name and number | |
| Option: | Integrated text messaging | |
| Mount: | DZUS-rail | |
| Physical: | 5.7 x 1.9 x 5.0 in. | |
| Weight: | 0.8 lb. (0.3kg) | |
| Depth Behind Panel: | 6.5in. (16.5cm) | |
| Backlight Keypad: | Standard dialing with in-call DTMF and text input | |
| Programmed Dialing: | 500 16-digit phone numbers with 16-char name | |
| Programmable Text Modes: | 200 customized and grouped messages | |
| Power: | 10-32 VDC @ 100ma max | |
| Connectors: | DB-25 male (2) | |
| Tactical Dialer | | |
| Display: | Dimmable LEDs and backlighting | |
| Toggles: | Pull-to-throw | |
| Physical: | 5.75 x 1.4 x 1.75 / 0.3 lb. | |
| Aviation Transceiver | | |
| Compliance: | DO-160D; STC (various) | |
| Power: | 12-32 VDC | |
| Physical: | 10.25 x 4.8 x 2.9 in. / 4.32 lb. Tray: 10.75 x 2.9 x 0.75 in. | |
| Single Iridium [®] Antenna | | |
| Compliance: | TSO C-144, DO-160D | |
| Physical: | 5.0 x 2.2 x 0.75 in. / 0.6 lb. | |
| Dual Iridium® Antenna | | |
| Compliance: | TSO C-144, DO-160D | |
| Physical: | 5.0 x 2.2 x 0.75 in. / 0.6 lb. | |

To Find Out More

Visit us online at: aerospace.honeywell.com/skyconnect

| Product SpecificationsITEMSPECBasic Transceiver Specs:Dual Channel (Voice, Tracking, and Messaging)Regulatory Compliance:DD16OF (Including +55000 Alt, +85/+55 Temp)Weight:4.4 lbs. Max. (Modem dependent)Length // Width / Height:10.25 Inches L / 2 Inches W / 4 Inches HPower Requirements:12-32VDC, 2.5 Amp @ 28VDC, 3.5 Amp @ 14VDCTransmit Power Average:1.5 watts per LBTMounting:Quick release tray, 4+#B holes, any configurationTransmission rate:2.4Kbps voice and data (10Kbps with compression)Operating Frequency:1616-16265 GHzPorts (Plain Old Telephone Service) / 4 Wire Audio output 5 en RS232 Ports (Msyr, CPS/Mx, PC, Sml / 2) 2 en ARINC 429 (Plupts). Le adNINC 429 Output 8 en discrete inputs 0-36VDC. Sink 200ma Max. 4 Discrete output, Max Voltage, 36VDC, sink 200ma 1 en USB - PC Data connection 1 en USB - PC Data connection 2 en ARINC 429Hi/Lo Speed-Althudo, Lat/Lon, Track, Ground Speed, Cross track error, Desired Track • Ostarnee to waypoint, Bearing to waypoint, magnetic variation • F | | | |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| ITEMSPECBasic Transceiver Specs:Dual Channel (Voice, Tracking, and Messaging)Regulatory Compliance:DD150F (Including +555000 Alt, +85/-55 Temp)Weight:4.4 lbs. Max. (Modern dependent)Length / Width / Height:10.25 Inches / 2.9 Inches W / 4.8 Inches HPower Requirements:12-32VDC, 2.5 Amp @ 24VDC, 3.5 Amp @ 14VDCTransmit Power Average:1.5 watts per LBTMounting:Quick release tray, 4+#8 holes, any configurationTransmit Power Average:1.616-1.6265 GHzOperating Frequency:1.616-1.6265 GHzInputs/Outputs:POTS (Plain Old Telephone Service) / 4 Wire Audio output 5 en 82.32 Ports (Msgr, CPS/Aux, PC, Sml / 20) 2 en ARINC 429 Inputs 1.e AudINC 429 Output 8 en discrete inputs 0.34VDC, Sink 200ma Max, 4 Discrete outputs, Max Voltage, 36VDC, sink 200ma 1 en USB - PC Data connection 1 en Elsenert Port for configurationData Configuration 1 en USB - PC Data connection 1 en Elsenert Port for configuration 2 es PAINC 429 Unputs 1 en AMINC 429H//Lo Speed- Altitude Lat/Lon, Track Ground Speed, Cross track error, Desired Track • Distance to waypoint, Bearing to waypoint, magnetic variation • Flight Plan dataRecording RateUser configurableGPS Internal:NMEAMMEA MessagesGSV, RMC, GSA, GGA, GLL, VTG, TXTRecording RateUser configurableGPS Internal:Yaries with user selected params and rates, minimum ~350hrsTemperature Monitors4 with user selected params and rates, minimum ~350hrsTemperature Monitors4 with user selected params and rates, minimum ~350hrsRe | SKY CONNECT TRACKER SYSTEM III | | |
| Data Channel (Voice, Tracking, and Messaging)Regulatory Compliance:D0160F (Including +55000 Alt, +85/-55 Temp)Weight:4.4 lbs. Max. (Modem dependent)Length / Width / Height:10.25 Inches I / 2.9 Inches W / 4.8 Inches HPower Requirements:12-32VDC, 2.5 Amp @ 28VDC, 3.5 Amp @ 14VDCTransmit Power Average:1.5 watts par LBTMounting:Quick release tray, 4+#8 holes, any configurationTransmit Sion rate:2.4Kbps voice and data (10Kbps with compression)Operating Frequency:1616-1.6265 GFzPOTS (Plain Old Telephone Service) / 4 Wire Audio outputSea AllNC 429 Inputs. 1ea ARINC 429 OutputBe a discret inputs 0-34VDC, Sink 200maI.e. USB - PC Data connectionI.e. USB - PC Data connectionBerS External ARINC429:Hi/Lo Speed*Altitude, Lat/Lon, Track, Ground Speed, Cross track error, Desired Track•I.Stance to waypoint, Bearing to waypoint, magnetic variation*I.Stance to waypoint, Bearing to waypoin | | | |
| Regulatory Compliance:D0160F (Including +55000 Alt, +85/+55 Temp)Weight:4.4 lbs. Max. (Modem dependent)Length / Width / Height:10.25 Inches I. / 2.9 Inches W / 4.8 Inches HPower Requirements:1.5 watts par LBTMounting:Quick release tray, 4-#8 holes, any configurationTransmistion rate:2.4 KDps voice and data (10Kbps with compression)Operating Frequency:1.616-1.6265 GHzInputs/Outputs:POTS (Magr. GPS/Aux, PC, Sim L/2) 2 ea. ARINC 429 Inputs, 1 ea ARINC 429 Output 8 ea discrete inputs 0-36VDC. Sink 200ma Max, 4 Discrete outputs, Max Voitaga, SOVDC aink 200ma 1 ea. USB - PC Data connection 1 ea. USB - PC Data consection 1 ea. USB - PC Data consection 2 ea. ARINC 429 InputsBroch Carding Rate <td< td=""><td>ITEM</td><td>SPEC</td></td<> | ITEM | SPEC | |
| Weight:4.4 lbs.Max.(Modem dependent)Length / Width / Height:10.25 Inches L / 2.9 Inches W / 4.8 Inches HPower Requirements:12-32VDC, 2.5 Amp @ 28VDC, 3.5 Amp @ 14VDCTransmit Power Average:1.5 watts per LBTMounting:Quick release tray, 4.4% holes, any configurationTransmitsion rate:2.4Kbps voice and data (10Kbps with compression)Operating Frequency:1.616-1.6265 GHzOperating Frequency:1.616-1.6265 GHzOperating Frequency:1.616-1.6265 GHzInputs/Outputs:8.e. RS232 Ports (Msyr, GPS/Aux, PC, Sim 1/2)2 e.a. RAIN C 429 Ionyt. La RAIN C 429 Output8.e. RS232 Ports (Msyr, GPS/Aux, PC, Sim 1/2)2 e.a. RAIN C 429 Ionyt. La RAIN C 429 Output8.e. discrete inputs 0-36VDC, Sink 200ma1 e.a. USB - PC Data connection1.a. Ethermet Port for configurationData PositionTracking source prioritization/redundancy allows simultaneous use of 3 separate GPS sourcesGPS Data*Altitude, Lat/Lon, Track, Ground Speed, Cross track error, Desired TrackH/LO Speed*Altitude, Lat/Lon, Track, Ground Speed, Cross track error, Desired TrackGSD RaudGarmin, Honeywell, Trimble and other standard ADF formats4800 BaudNMEARecording RateUser configurableGPS Internat:User configurableGPS Internat:User configurableGPS Internat:Varies with user selected params and rates, minimum -350 hrsTemperature Monitoring4 with user selected params and rates, minimum -350 hrsTemperature MonitoringSistrel Input a | Basic Transceiver Specs: | Dual Channel (Voice, Tracking, and Messaging) | |
| Length / Width / Height:10.25 Inches L / 2.9 Inches W / 4.8 Inches HPower Requirements:12-32VDC, 2.5 Amp @ 28VDC, 3.5 Amp @ 14VDCTransmit Power Average:1.5 watts per LBTMounting:Quick release tray, 4-#8 holes, any configurationTransmission rate:2.4Kbps voice and data (10Kbps with compression)Operating Frequency:1.616-16265 GHzDystample Frequency:1.616-16265 GHzInputs/Outputs:BARNC 429 Inputs, 1ea ARINC 429 OutputBe. RS23 2 Ports (Msgr, GPS/Aux, PC, Sim 1/2)2.e. ARINC 429 Inputs, 1.e. ARINC 429 OutputBe. RS25 Ports (Msgr, GPS/Aux, PC, Sim 1/2)2.e. ARINC 429 Inputs, 1.e. ARINC 429 OutputBe. RS25 Ports (Msgr, GPS/Aux, PC, Sim 1/2)2.e. ARINC 429 Inputs, 1.e. ARINC 429 OutputBe. RS25 Ports (Msgr, GPS/Aux, PC, Sim 1/2)2.e. ARINC 429 Inputs, 1.e. ARINC 429 OutputBes Atter Inputs - De Data connection1.e. Ethernet Port for configurationData PositionTracking source prioritization/redundancy allows simultaneous use of 3 separate GPS sourcesGPS External ARINC429:-Altitude, Lat/Lon, Track, Ground Speed, Cross track error, Desired Track - Distance to waypoint, Bearing to waypoint, magnetic variation - Flight Plan dataRecording RateUser configurableGPS Internal:User configurableGPS Internal:StorageMEA MessagesGSV, RMC, GSA, GGA, GLL, VTG, TXTRecording RateUser configurableFlight Data MonitoringYavies with user selected params and rates, minimum -350hrsTemperature Monitors4 with user selected params and rates, minimum -350hrs <td>Regulatory Compliance:</td> <td>D0160F (Including +55000 Alt, +85/-55 Temp)</td> | Regulatory Compliance: | D0160F (Including +55000 Alt, +85/-55 Temp) | |
| Power Requirements12-32VDC, 2.5 Amp @ 28VDC, 3.5 Amp @ 14VDCTransmit Power Average:1.5 watts per LBTMounting:Quick release tray, 4-#8 holes, any configurationTransmission rate:2.4Kbps voice and data (10Kbps with compression)Operating Frequency:1.616-1.6265 GHzPOTS (Plain Old Telephone Service) / 4 Wire Audio output 5 ea RS/32 Ports (Msgr. GPS/Aux, PC, Sim /20) 2 ea, ARINC 4/29 Inputs, 1 ea ARINC 4/29 Output 8 ea discrete inputs 0-36VDC, Sink 200ma 1 ea LSB -PC Data connection 1 ea LSB -PC Data connection 2 PC Data Cons track error, Desired Track • Distance to wayooint, Bearing to wayooint, magnetic variation • Flight Plan dataRecording RateUser configurable GPS Internat:MEA MessagesGSV, RMC, GSA, GGA, GLL, VTG, TXT Recording RatePG So Istorage4GB accessible via the Ethernet PortRecording TimeVaries with user selected params and rates, minimum | Weight: | 4.4 lbs. Max. (Modem dependent) | |
| Tansmit Power Average:1.5 watts por LBTMounting:Quick release tray, 4-#8 holes, any configurationTransmission rate:2.4Kbps voice and data (10Kbps with compression)Operating Frequency:1.616-1.6265 GHzPDTS (Plain Old Telephone Service) / 4 Wire Audio output 5 ea. RS23 Ports (Msgr, CFS/Aux, PC, Sm1/2) 2 ea. ARINC 429 Inputs, L ea ARINC 429 Output 8 ea. discrete inputs 0-36VDC. Sink 200ma Max. 4 Discrete outputs, Max Va00ma Max. 4 Discrete outputs outputs. 4 | Length / Width / Height: | 10.25 Inches L / 2.9 Inches W / 4.8 Inches H | |
| Mounting: Quick release tray, 4+#8 holes, any configuration Transmission rate: 2.4Kbps voice and data (10Kbps with compression) Operating Frequency: 1.616-1.6265 GHz Inputs/Outputs: POTS (Plain Old Telephone Service) / 4 Wire Audio output 5 ea. RS32 2P Output 8 ea. RS32 4P Output 8 ea. discrete inputs 0-35VDC, Sink 200ma Max 4 Discrete outputs, Max Voitage, 36VDC, sink 200ma 1 ea. USB - PC Data connection 1 ea. Ethernet Port for configuration Data Position - GPS Data Tracking source prioritization/redundancy allows simultaneous use of 3 separate GPS sources GPS External ARINC429: - Altitude, Lat/Lon, Track, Ground Speed, Cross track error, Desired Track - Distance to waypoint, Bearing to waypoint, magnetic variation - Flight Plan data Recording Rate User configurable GPS External RS232: - 9600 Baud Garmin, Honeywell, Trimble and other standard ADF formats 4800 Baud NMEA Recording Rate User configurable GPS Internal: - NMEA Recording Rate User configurable GBB Flight Data Monitoring - SD Storage 4GB accessible via the Ethernet Port Recording Time Varies with user selectable Quer the air al | Power Requirements: | 12-32VDC, 2.5 Amp @ 28VDC, 3.5 Amp @ 14VDC | |
| Transmission rate: 2.4Kbps voice and data (10Kbps with compression) Operating Frequency: 1.616-1.6265 GHz PDTS (Plain Old Telephone Service) / 4 Wire Audio output 5 ea. RS2 32 Ports (Magr, GPS/Aux, PC, SmJ /2) 2 ea ARINC 429 Jonupt. Inputs/Outputs: 8 ea discrete inputs 0-36VDC, Sink 200ma Max, 4 Discrete outputs, Max Voltage, 36VDC, sink 200ma 1 ea. USB - PC Data connection 1 ea. Ethernet Port for configuration Data Position • Altitude, Lat/Lon, Track, Ground Speed, Cross track error, Desired Track • Distance to waypoint, Bearing to waypoint, magnetic variation • Flight Plan data Recording Rate User configurable GPS External RS232: 9600 Baud GPS External RS232: 9600 Baud Garmin, Honeywell, Trimble and other standard ADF formats 4800 Baud NMEA Recording Rate User configurable GPS Internal: User configurable GPS Internal: User configurable Tight Plant data 9000 Recording Rate User configurable User configurable GPS Internal: VMEA NMEA Messages GSV, RMC, GSA, GGA, GLL, VTG, TXT Recording Rate User configurable Tight Data Monitoring 4GB accessible via the Ethernet Port Recording Rate <td>Transmit Power Average:</td> <td>1.5 watts per LBT</td> | Transmit Power Average: | 1.5 watts per LBT | |
| Operating Frequency: 1.616-1.6265 GHz POTS (Plain Old Telephone Service) / 4 Wire Audio output 5 ea. RS232 Ports (Msgr, GPS/Aux, PC, Sim 1/2) 2 ea ARINC 429 Inputs, 1 ea ARINC 429 Output 8 ea. discrete inputs 0.36VDC, sink 200ma Max. 4 Discrete outputs, Max Voltage, 36VDC, sink 200ma 1 ea. USB - PC bata connection 1 ea. USB - PC sources GPS Data Tracking source prioritization/redundancy allows simultaneous use of 3 separate GPS sources GPS External ARINC429: • Attitude, Lat/Lon, Track, Ground Speed, Cross track error, Desired Track • Distance to waypoint, Bearing to waypoint, magnetic variation • Flight Plan data Recording Rate User configurable GPS External RS232: 9600 Baud 9600 Baud Garmin, Honeywell, Trimble and other standard ADF formats 4800 Baud NMEA Recording Rate User configurable GPS Internat: UMEA MMEA Messages GSV, RMC, GSA, GGA, GLL, VTG, TXT Recording Rate User configurable Flight Data Monitoring Yorides and ditional minute of operation post power loss Recording Time Varies with user selected params and rates, minimum -350hrs Temperature Monitors 4 with user selectable Over the air alert threshol | Mounting: | Quick release tray, 4-#8 holes, any configuration | |
| POTS (Plain Old Telephone Service) / 4 Wire Audio output Sea. RS232 Ports (Msgr, GPS/Aux, PC, Sim 1/2) 2 ea. ARINC 429 Inputs, 1 ea ARINC 429 Output 8 ea. discrete inputs - 0.54VC, Sink 200ma Max. 4 Discrete outputs, Max Voltage, 36VDC, sink 200ma 1 ea. USB - PC Data connection 2 ea. Attinude, Lat/Lon, Track, Ground Speed, Cross track error, Desired Track + ViLo Speed • Altitude, Lat/Lon, Track, Ground Speed, Cross track error, Desired Track • Plight Data data Recording Rate User configurable GPS External RS232: 9600 Ba | Transmission rate: | 2.4Kbps voice and data (10Kbps with compression) | |
| Sea. RS232 Ports (Msgr. GPS/Aux, PC, Sim 1/2) 2 ea. ARINC 429 Inputs, 1 ea ARINC 429 Unputs 8 ea. discrete input or SOVDC. Sink 200ma Max. 4 Discrete outputs, Max Voltage, 36VDC, sink 200ma 1 ea. USB - PC Data connection 1 ea. USB - PC Data connection 1 ea. USB - PC Data connection 3 separate GPS sourcesData PositionTracking source prioritization/redundancy allows simultaneous use of 3 separate GPS sourcesGPS External ARINC429:Hi/Lo Speed• Altitude, Lat/Lon, Track, Ground Speed, Cross track error, Desired Track • Distance to waypoint, Bearing to waypoint, magnetic variation • Flight Plan dataRecording RateUser configurableGPS External RS232:9600 BaudGarmin, Honeywell, Trimble and other standard ADF formats4800 BaudNMEARecording RateUser configurableGPS Internal:Other ConfigurableMEA MessagesGSV, RMC, GSA, GGA, GLL, VTG, TXTRecording RateUser configurableEtight Data MonitoringDiscrete Input activity, Call Logs, Signal StrengthSD Storage4GB accessible via the Ethernet PortRecording TimeVaries with user selected params and rates, minimum ~350hrsTemperature Monitors5 Jac et alutitional minute of operation post power lossRecord Autonomous EventsDiscrete Input activity, Call Logs, Signal StrengthDual ARINC429 Inputs:100ms-60sUser selectable Recordable Labels64Additional GPS Labels Recorded23Is reselectable Recordable Labels64Additional GPS Labels Recorded23Sus selectable | Operating Frequency: | 1.616-1.6265 GHz | |
| GPS DataTracking source prioritization/redundancy allows simultaneous use of 3 separate GPS sourcesGPS External ARINC429:• Altitude, Lat/Lon, Track, Ground Speed, Cross track error, Desired Track • Distance to waypoint, Bearing to waypoint, magnetic variation • Flight Plan dataRecording RateUser configurableGPS External RS232:9600 Baud9600 BaudGarmin, Honeywell, Trimble and other standard ADF formats4800 BaudNMEARecording RateUser configurableGPS Internal:User configurableGPS Internal:User configurableMEA MessagesGSV. RMC, GSA, GGA, GLL, VTG, TXTRecording RateUser configurableFlight Data MonitoringVaries with user selected params and rates, minimum ~350hrsSD Storage4GB accessible via the Ethernet PortRecording TimeVaries with user selected params and rates, minimum ~350hrsTemperature Monitors4 with user selectable Over the air alert thresholdsCapacitive Keep Alive CircuitProvides an additional minute of operation post power lossRecording Time10 circuit and dutional minute of operation post power lossRecorded Autonomous EventsDiscrete Input activity, Call Logs, Signal StrengthDual ARINC429 Inputs:10 oms~60sUser selectable Recordable Labels64Additional GPS Labels Recorded23User selectable Sampling Rates10 oms~60sOTA Alert Labels and sampling groupsAAccelerometer:3AisOrientation at user discretionRecording RateUser confi | Inputs/Outputs: | 5 ea. RS232 Ports (Msgr, GPS/Aux, PC, Sim1/2) 2 ea. ARINC 429 Inputs, 1 ea ARINC 429 Output 8 ea. discrete inputs 0-36VDC, Sink 200ma Max. 4 Discrete outputs, Max Voltage, 36VDC, sink 200ma 1 ea. USB - PC Data connection | |
| GPS Data3 separate GPS sourcesGPS External ARINC429:• Altitude, Lat/Lon, Track, Ground Speed, Cross track error, Desired Track • Distance to waypoint, Bearing to waypoint, magnetic variation • Flight Plan dataRecording RateUser configurableGPS External RS232:9600 BaudGarmin, Honeywell, Trimble and other standard ADF formats4800 BaudMAEARecording RateUser configurableGPS Internal:User configurableMEA MessagesGSV, RMC, GSA, GGA, GLL, VTG, TXTRecording RateUser configurableFlight Data MonitoringUser configurableSD Storage4GB accessible via the Ethernet PortRecording TimeVaries with user selected params and rates, minimum ~350hrsTemperature Monitors4 with user selectable Over the air alert thresholdsCapacitive Keep Alive CircuitProvides an additional minute of operation post power lossRecorded Autonomous EventsDiscrete Input activity, Call Logs, Signal StrengthDual ARINC429 Inputs:23User selectable Recordable Labels64Additional GPS Labels Recorded23User selectable Sampling Rates100ms-60sOTA Alert Labels and sampling groups4AxisOrientation at user discretionRecording RateUser configurable | | | |
| Hi/Lo Speed•Altitude, Lat/Lon, Track, Ground Speed, Cross track error, Desired Track •Distance to waypoint, Bearing to waypoint, magnetic variation •Fight Plan dataRecording RateUser configurableGPS External RS232:Garmin, Honeywell, Trimble and other standard ADF formats4800 BaudGarmin, Honeywell, Trimble and other standard ADF formats4800 BaudUser configurableGPS Internal:User configurableGPS Internal:User configurableFlight Data MonitoringGSV, RMC, GSA, GGA, GLL, VTG, TXTRecording RateUser configurableFlight Data MonitoringYaries with user selected params and rates, minimum ~350hrsSD Storage4 With user selectable Over the air alert thresholdsCapacitive Keep Alive CircuitProvides an additional minute of operation post power lossRecorded Autonomous EventsDiscrete Input activity, Call Logs, Signal StrengthDual ARINC429 Inputs:100ms-60sUser selectable Recorded Labels64Additional GPS Labels Recorded23User selectable Sampling Rates100ms-60sOTA Alert Labels and sampling groups4Accelerometer:3 AxisOrientation at user discretionSeretoring mate is configurableRecording RateUser configurable | GPS Data | | |
| Hi/Lo SpeedDistance to waypoint, Bearing to waypoint, magnetic variation +Fight Plan dataRecording RateUser configurableGPS External RS232:Garmin, Honeywell, Trimble and other standard ADF formats4800 BaudMMEARecording RateUser configurableGPS Internal:User configurableGPS Internal:GSV, RMC, GSA, GGA, GLL, VTG, TXTNMEA MessagesGSV, RMC, GSA, GGA, GLL, VTG, TXTRecording RateUser configurableFlight Data MonitoringVaries with user selected params and rates, minimum ~350hrsSD Storage4 GB accessible via the Ethernet PortRecording TimeVaries with user selected params and rates, minimum ~350hrsTemperature Monitors4 with user selectable Over the air alert thresholdsCapacitive Keep Alive CircuitProvides an additional minute of operation post power lossRecorded Autonomous EventsDiscrete Input activity, Call Logs, Signal StrengthDual ARINC429 Inputs:100ms-60sUser selectable Recordable Labels64Additional GPS Labels Recorded23User selectable Sampling Rate100ms-60sOTA lert Labels and sampling groups4AxisOrientation at user discretionAxisOrientation at user discretionRecording RateUser configurable | | | |
| GPS External RS232:9600 BaudGarmin, Honeywell, Trimble and other standard ADF formats4800 BaudNMEARecording RateUser configurableGPS Internal:NMEA MessagesGSV, RMC, GSA, GGA, GLL, VTG, TXTRecording RateUser configurable Flight Data Monitoring SD Storage4GB accessible via the Ethernet PortRecording TimeVaries with user selected params and rates, minimum ~350hrsTemperature Monitors4 with user selectable Over the air alert thresholdsCapacitive Keep Alive CircuitProvides an additional minute of operation post power lossRecorded Autonomous EventsDiscrete Input activity, Call Logs, Signal StrengthDual ARINC429 Inputs:100ms-60sUser selectable Sampling Rates100ms-60sOTA Alert Labels and sampling groups4Accelerometer:3 AxisOrientation at user discretionSteretionRecording RateUser configurable | Hi/Lo Speed | Distance to waypoint, Bearing to waypoint, magnetic variation | |
| 9600 BaudGarmin, Honeywell, Trimble and other standard ADF formats9600 BaudNMEARecording RateUser configurableGPS Internal:NMEA MessagesGSV, RMC, GSA, GGA, GLL, VTG, TXTRecording RateUser configurableFlight Data MonitoringSD Storage4GB accessible via the Ethernet PortRecording TimeVaries with user selected params and rates, minimum ~350hrsTemperature Monitors4 with user selectable Over the air alert thresholdsCapacitive Keep Alive CircuitProvides an additional minute of operation post power lossRecorded Autonomous EventsDiscrete Input activity, Call Logs, Signal StrengthDual ARINC429 Inputs:User selectable Recordable Labels64Additional GPS Labels Recorded23User selectable Sampling Rates100ms-60sOTA Alert Labels and sampling groups4Accelerometer:3 AxisRecording RateUser configurable | Recording Rate | User configurable | |
| 4800 BaudNMEARecording RateUser configurableGPS Internal:GSV, RMC, GSA, GGA, GLL, VTG, TXTNMEA MessagesGSV, RMC, GSA, GGA, GLL, VTG, TXTRecording RateUser configurableFlight Data MonitoringSD Storage4GB accessible via the Ethernet PortRecording TimeVaries with user selected params and rates, minimum ~350hrsTemperature Monitors4 with user selectable Over the air alert thresholdsCapacitive Keep Alive CircuitProvides an additional minute of operation post power lossRecorded Autonomous EventsDiscrete Input activity, Call Logs, Signal StrengthDual ARINC429 Inputs:User selectable Recordable LabelsAdditional GPS Labels Recorded23User selectable Sampling Rates100ms-60sOTA Alert Labels and sampling groups4AxisOrientation at user discretionRecording RateUser configurable | GPS External RS232: | | |
| Recording RateUser configurableGPS Internal:NMEA MessagesGSV, RMC, GSA, GGA, GLL, VTG, TXTRecording RateUser configurableFlight Data MonitoringSD Storage4GB accessible via the Ethernet PortRecording TimeVaries with user selected params and rates, minimum ~350hrsTemperature Monitors4 with user selectable Over the air alert thresholdsCapacitive Keep Alive CircuitProvides an additional minute of operation post power lossRecorded Autonomous EventsDiscrete Input activity, Call Logs, Signal StrengthDual ARINC429 Inputs:100ms-60sUser selectable Sampling Rates100ms-60sOTA Alert Labels and sampling groups4Accelerometer:3 AxisStarisOrientation at user discretionRecording RateUser configurable | 9600 Baud | Garmin, Honeywell, Trimble and other standard ADF formats | |
| GPS Internal:GPS Internal:NMEA MessagesGSV, RMC, GSA, GGA, GLL, VTG, TXTRecording RateUser configurableFlight Data MonitoringSD Storage4GB accessible via the Ethernet PortRecording TimeVaries with user selected params and rates, minimum ~350hrsTemperature Monitors4 with user selectable Over the air alert thresholdsCapacitive Keep Alive CircuitProvides an additional minute of operation post power lossRecorded Autonomous EventsDiscrete Input activity, Call Logs, Signal StrengthDual ARINC429 Inputs:User Selectable Recordable Labelsdditional GPS Labels Recorded23User selectable Sampling Rates100ms-60sOTA Alert Labels and sampling groups4Accelerometer:3 AxisOrientation at user discretionRecording RateUser configurable | 4800 Baud | NMEA | |
| NMEA MessagesGSV, RMC, GSA, GGA, GLL, VTG, TXTRecording RateUser configurableFlight Data Monitoring4GB accessible via the Ethernet PortSD Storage4GB accessible via the Ethernet PortRecording TimeVaries with user selected params and rates, minimum ~350hrsTemperature Monitors4 with user selectable Over the air alert thresholdsCapacitive Keep Alive CircuitProvides an additional minute of operation post power lossRecorded Autonomous EventsDiscrete Input activity, Call Logs, Signal StrengthDual ARINC429 Inputs:4User Selectable Recordable Labels64Additional GPS Labels Recorded23User selectable Sampling Rates100ms-60sOTA Alert Labels and sampling groups4AxisOrientation at user discretionRecording RateUser configurable | Recording Rate | User configurable | |
| Recording RateUser configurableFlight Data MonitoringSD Storage4GB accessible via the Ethernet PortRecording TimeVaries with user selected params and rates, minimum ~350hrsTemperature Monitors4 with user selectable Over the air alert thresholdsCapacitive Keep Alive CircuitProvides an additional minute of operation post power lossRecorded Autonomous EventsDiscrete Input activity, Call Logs, Signal StrengthDual ARINC429 Inputs:User selectable Recordable LabelsUser selectable Recordable Labels64Additional GPS Labels Recorded23User selectable Sampling Rates100ms-60sOTA Alert Labels and sampling groups4Accelerometer:3 AxisOrientation at user discretionRecording RateUser configurable | GPS Internal: | | |
| Flight Data MonitoringSD Storage4GB accessible via the Ethernet PortRecording TimeVaries with user selected params and rates, minimum ~350hrsTemperature Monitors4 with user selectable Over the air alert thresholdsCapacitive Keep Alive CircuitProvides an additional minute of operation post power lossRecorded Autonomous EventsDiscrete Input activity, Call Logs, Signal StrengthDual ARINC429 Inputs:User Selectable Recordable LabelsUser Selectable Recordable Labels64Additional GPS Labels Recorded23User selectable Sampling Rates100ms-60sOTA Alert Labels and sampling groups4Accelerometer:3 AxisOrientation at user discretionRecording RateUser configurable | NMEA Messages | GSV, RMC, GSA, GGA, GLL, VTG, TXT | |
| SD Storage4GB accessible via the Ethernet PortRecording TimeVaries with user selected params and rates, minimum ~350hrsTemperature Monitors4 with user selectable Over the air alert thresholdsCapacitive Keep Alive CircuitProvides an additional minute of operation post power lossRecorded Autonomous EventsDiscrete Input activity, Call Logs, Signal StrengthDual ARINC429 Inputs:User Selectable Recordable LabelsAdditional GPS Labels Recorded23User selectable Sampling Rates100ms-60sOTA Alert Labels and sampling groups4Accelerometer:3 AxisOrientation at user discretionRecording RateUser configurable | Recording Rate | User configurable | |
| Recording TimeVaries with user selected params and rates, minimum ~350hrsTemperature Monitors4 with user selectable Over the air alert thresholdsCapacitive Keep Alive CircuitProvides an additional minute of operation post power lossRecorded Autonomous EventsDiscrete Input activity, Call Logs, Signal StrengthDual ARINC429 Inputs:User Selectable Recordable Labelsdditional GPS Labels Recorded23User selectable Sampling Rates100ms-60sOTA Alert Labels and sampling groups4Accelerometer:3 AxisOrientation at user discretionRecording RateUser configurable | Flight Data Monitoring | | |
| Temperature Monitors4 with user selectable Over the air alert thresholdsCapacitive Keep Alive CircuitProvides an additional minute of operation post power lossRecorded Autonomous EventsDiscrete Input activity, Call Logs, Signal StrengthDual ARINC429 Inputs:User Selectable Recordable Labels4 dditional GPS Labels Recorded23User selectable Sampling Rates100ms-60sOTA Alert Labels and sampling groups4Accelerometer:3 AxisOrientation at user discretionRecording RateUser configurable | SD Storage | 4GB accessible via the Ethernet Port | |
| Capacitive Keep Alive CircuitProvides an additional minute of operation post power lossRecorded Autonomous EventsDiscrete Input activity, Call Logs, Signal StrengthDual ARINC429 Inputs:User Selectable Recordable Labels64Additional GPS Labels Recorded23User selectable Sampling Rates100ms-60sOTA Alert Labels and sampling groups4Accelerometer:3 AxisOrientation at user discretionRecording RateUser configurable | Recording Time | Varies with user selected params and rates, minimum ~350hrs | |
| Recorded Autonomous EventsDiscrete Input activity, Call Logs, Signal StrengthDual ARINC429 Inputs:User Selectable Recordable Labels64Additional GPS Labels Recorded23User selectable Sampling Rates100ms-60sOTA Alert Labels and sampling groups4Accelerometer:3 AxisOrientation at user discretionRecording RateUser configurable | Temperature Monitors | 4 with user selectable Over the air alert thresholds | |
| Dual ARINC429 Inputs: User Selectable Recordable Labels 64 Additional GPS Labels Recorded 23 User selectable Sampling Rates 100ms-60s OTA Alert Labels and sampling groups 4 Accelerometer: 3 Axis Orientation at user discretion Recording Rate | Capacitive Keep Alive Circuit | Provides an additional minute of operation post power loss | |
| User Selectable Recordable Labels64Additional GPS Labels Recorded23User selectable Sampling Rates100ms-60sOTA Alert Labels and sampling groups4Accelerometer:33 AxisOrientation at user discretionRecording RateUser configurable | Recorded Autonomous Events | Discrete Input activity, Call Logs, Signal Strength | |
| Additional GPS Labels Recorded23User selectable Sampling Rates100ms-60sOTA Alert Labels and sampling groups4Accelerometer:33 AxisOrientation at user discretionRecording RateUser configurable | Dual ARINC429 Inputs: | | |
| User selectable Sampling Rates 100ms-60s OTA Alert Labels and sampling groups 4 Accelerometer: 3 3 Axis Orientation at user discretion Recording Rate User configurable | User Selectable Recordable Labels | 64 | |
| OTA Alert Labels and sampling groups 4 Accelerometer: 3 3 Axis Orientation at user discretion Recording Rate User configurable | Additional GPS Labels Recorded | 23 | |
| sampling groups 4 Accelerometer: 3 3 Axis Orientation at user discretion Recording Rate User configurable | User selectable Sampling Rates | 100ms-60s | |
| 3 Axis Orientation at user discretion Recording Rate User configurable | | 4 | |
| Recording Rate User configurable | | | |
| | 3 Axis | Orientation at user discretion | |
| | Recording Rate | User configurable | |
| | | User configurable thresholds | |

Honeywell Aerospace

1944 East Sky Harbor Circle Phoenix, AZ 85034 aerospace.honeywell.com

Honeywell